



DESCRIPTION

METHOD OF SETTING AUDIO OUTPUT LEVEL
AND DEVICE THEREFOR

5

This application is a U.S. national stage application of PCT international application PCT/JP2004/019444.

TECHNICAL FIELD

10 The present invention relates to a method of setting the audio output level for a device equipped with an audio output.

BACKGROUND ART

15 Currently, setting of the audio output level for a device equipped with an audio output, such as a television set or audio equipment, is generally made through remote control with a remote control unit, as well as through setting with the main unit of the device. Therefore, the main unit and remote control unit each have up/down buttons for the volume level ~~up/down respectively being allocated~~, where these
20 volume change buttons are operated as required when using a television set or audio equipment. A volume adjustment button is usually easy to operate because it is frequently used.

25 Meanwhile, a television set or audio equipment usually has ~~its~~ a volume range from an adequately large ~~volume~~ volume, as compared to ~~one~~ a volume in regular use, to silence. The maximum available volume of the device is not necessarily equal to ~~an allowable~~ a normal level in regular use.

Among conventional methods of setting the audio output level, a method of automatically adjusting the volume level according to ambient circumstances is disclosed in Japanese Patent Unexamined Publication No. H08-97654 (hereinafter, referred to as "patent literature 1"). Further, a method in which minimum and maximum input levels are preliminarily set when amplifying audio signals with a variable gain-amplifier, amplifier is disclosed in Japanese Patent Unexamined Publication No. H10-294990 (hereinafter, referred to as "patent literature 2").

As mentioned above, the operation of changing the volume setting for a television set or audio equipment is desirably easy because the operation is frequently performed. This ~~instead~~ may cause the volume level to increase more than necessary if the operable part is accidentally touched or if an infant innocently changes the volume level.

Even if the volume level is automatically changed according to ambient circumstances as in the invention described in patent literature 1, the above-mentioned problems ~~can not~~ cannot be solved because the basic audio level is set by the user.

Meanwhile, a maximum output volume may be restricted as in the invention described in patent literature 2, which ~~is~~ poses an obstacle because a required volume level may not be available in some operation environments.

Further, in a television set or audio equipment, turning on the power again after turning off the power with the volume level ~~remaining~~ at a high ~~setting~~, setting causes too large a sound to burst out from the device because the previous audio output level is retained.

Another problem is, if the audio output level has been changed while the device is controlled to be in a silent state ~~for its controlling, releasing~~ ending the silent state unexpectedly causes too large a sound to burst out from the device.

5

SUMMARY OF THE INVENTION

In order to solve these problems, with a method of setting the audio output level for a device equipped with an audio output, according to the present invention, a range of the audio output level in regular use is set as ~~a threshold; if~~ a threshold. If an operation is ~~made for setting performed to set~~ the audio output level ~~that exceeds to~~ exceed the range of the audio output level having been set, a request is made for an acknowledgment that the operation of changing the audio output level is appropriate; and only if a reply is given, ~~the setting is~~ the setting changed.

Further, a method of setting the audio output level according to the present invention is characterized in that the initial audio output level is automatically changed when the device is next used, if the audio output level has been set when previously used ~~so that the audio output level exceeds to exceed~~ the range of the audio output level in regular use.

Still, in a method of setting the audio output level according to the present invention, in a device that receives signals including audio information and performs audio output according to ~~the receive~~ received signals, the reception state of the receive signals is ~~checked; if~~ checked. If the operation of changing the audio output level setting is made during a silent period according to the reception state, the audio

25

output level setting is not changed, but notice that the audio output level setting is not to be changed is given. Alternatively, a request is made for an acknowledgment that the audio output level setting is to be changed, and only if such an acknowledgment is given, ~~the setting is~~
5 | the setting changed.

With the above-mentioned method, requesting the operator for an acknowledgment that the operation of changing the volume level currently being performed is one intended by the operator solves the problem in which an operating error causes audio output larger than
10 | necessary. Meanwhile, if the audio output level exceeding the range of the audio output level in regular use is selected for some reason, the problem is solved in which the retained audio output level setting causes audio output larger than necessary when the device is used again or the audio output is resumed.

15

BRIEF DESCRIPTION OF THE DRAWINGS

| Fig. 1 is a block diagram showing the makeup of ~~an~~ a device for setting the audio output level according to the first exemplary embodiment of the present invention.

20 | Fig. 2 is a flowchart showing a method of setting the audio output level according to the first exemplary embodiment of the present invention.

| Fig. 3 is a block diagram showing the makeup of ~~an~~ a device for setting the audio output level according to the second exemplary
25 | embodiment of the present invention.

Fig. 4 is a flowchart showing a method of setting the audio output level according to the second exemplary embodiment of the present

invention.

Fig. 5 is a block diagram showing the makeup of ~~an~~ a device for setting the audio output level according to the third exemplary embodiment of the present invention.

5 Fig. 6 is a flowchart showing a method of setting the audio output level according to the third exemplary embodiment of the present invention.

Fig. 7 is another flowchart showing a method of setting the audio output level according to the third exemplary embodiment of the
10 present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

A description ~~will be made~~ is provided for a method of setting the audio output level according to exemplary embodiments of the present
15 invention, using drawings.

FIRST EXEMPLARY EMBODIMENT

First, a description ~~will be made~~ is provided for an example makeup of devices realizing the method of setting the audio output
20 level according to the present invention. Here, in this application, the audio output level is assumed to refer to the degree of volume amplification output from an actual speaker or the like for audio signals.

Fig. 1 is a block diagram showing an example makeup according to
25 the exemplary embodiment of the present invention. In Fig. 1, the device for setting the audio output level according to the present invention has volume adjuster 1, volume setting means 2, output level

monitor 3, audio output level memory 4, replying means 5, volume changing means 6, and audio output means 7.

Here, audio output level memory 4 stores a threshold in setting a range of the audio output level, where the threshold is preliminarily
5 | set by the user. Hereinafter, a description ~~will be made~~ is provided for a case where an upper limit of the audio output level is set as this threshold.

Volume adjuster 1, used for inputting a volume adjusting command,
| corresponds to a volume change button on the remote control unit, or a
10 | button or knob for setting the volume level provided on the main unit. Volume adjuster 1 gives notice to volume setting means 2 that a request has been made for changing the audio output level setting (~~up~~
| ~~or down~~ raise or lower of the volume level).

Volume setting means 2 receives from volume adjuster 1 a request
15 | for changing the audio output level setting. Volume setting means 2 then gives notice to volume changing means 6 of changing the audio output level, if the request made from the volume adjuster 1 ~~for~~
| ~~changing the audio output level setting~~ is for lowering the volume level ~~down~~, or if the changed audio output level is lower than the upper limit
20 | of the audio output level that has been preliminarily set. Next, volume setting means 2 gives notice of changing the audio output level to volume changing means 6, if an acknowledgement is given by replying means 5 that the change is appropriate.

Meanwhile, if the request for volume setting made from the
25 | volume adjuster 1 is for raising the volume level ~~up~~, volume setting means 2 judges whether the changed audio output level exceeds the upper limit of the audio output level preliminarily set. This upper

limit of the audio output level, stored in audio output level memory 4, may be changeable according to an operator's instruction, or may be a fixed value preliminarily set.

If the changed audio output level exceeds the upper limit of the
5 audio output level preliminarily set, volume setting means 2 then gives notice to output level monitor 3 that a request has been made for
changing to the audio output level ~~exceeding to exceed~~ the upper limit.

Output level monitor 3 gives notice to the operator who has made the volume adjustment that the audio output level is to exceed the
10 upper limit preliminarily set after the audio output level setting is changed. The notice can be given with characters on the screen of a device provided with a display unit such as a television set, and/or with sound.

Replying means 5 receives a reply from the operator that the
15 volume adjustment is appropriate, when the output level monitor requests the operator for an acknowledgement that the audio output level setting is appropriate. Replying means 5 corresponds to a button provided on the remote control unit or main unit, in the same
way as ~~in~~ volume adjuster 1. Here, separately providing a reply
20 button may be avoided by adding the function of a reply button to another operation button. In this case, the relevant operation button is usually used for selecting its original function individually allocated. However, the button works as a reply button for output level monitor 3 for a certain period of time immediately after a request for an
25 acknowledgement is made by output level monitor 3. A certain period of time may be 3 seconds, for example. Here, if a reply is given ~~from~~ to replying means 5, output level monitor 3 may give notice again to the

operator that the setting of the audio output level has been enabled, to encourage the operator to change the audio output level.

Volume changing means 6 changes the audio output level according to an instruction for changing the audio output level setting given by volume setting means 2. Changing the audio output level is feasible with an electronic volume control device, for example.

Audio output means 7 outputs audio signals with their audio output level set by volume changing means 6.

Next, a description ~~will be made~~ is provided for the detailed processing procedure by volume setting means 2, using the flowchart in Fig. 2.

First, the process accepts an instruction for volume adjustment from volume adjuster 1 (step 102). Next, the process distinguishes the type of instruction for volume adjustment (step 103).

If the instruction is for raising the volume level ~~up~~, the process judges whether or not the volume level set by the instruction for volume adjustment exceeds the upper limit of the audio output level preliminarily set (step 104). Meanwhile, if ~~it~~ the instruction is for lowering the volume level ~~down~~, the process decreases the audio output level and then ends the volume adjustment (steps 111 and 112). In step 104, if the audio output level set with the instruction for volume adjustment does not exceed the upper limit, the process increases the audio output level and then ends the volume adjustment (steps 110 and 112).

In step 104, in case the audio output level set with the instruction for volume adjustment exceeds the upper limit, the process requests the operator for an acknowledgement that the operation is appropriate

(step 105).

When a reply is given from the operator within a certain period of time, the process increases the audio output level according to a subsequent instruction for raising the volume level-up, and then ends the volume adjustment (steps 106, 107, 108, and 112).

In step 106, if a reply is not given from the operator within a certain period of time, the process sets the audio output level to the upper limit and then ends the volume adjustment (steps 109 and 112). As a replying means from the operator, another operating means on the device can be used instead be used within a certain period of time after the request for an acknowledgement, not necessarily requiring a separate operating means.

In the above-mentioned makeup, the description is made for a method of setting the audio output level using one threshold.

However, plural thresholds can be set and stored. For example, the upper limit of the audio output level may be separately set according to a time frame in using the device. As an example, two different thresholds for daytime and nighttime are to be set, where the upper limit for daytime is to be different from that for nighttime.

~~In this case, it~~ This case is adequate acceptable as long as ~~these the~~ thresholds are set and stored ~~being associated in association~~ with the clock time information for using its threshold these thresholds. As a result, comparing the current clock time information obtained from the built-in clock means, with the stored clock time information, allows the audio output level to be controlled using the threshold having been set for the present time. Daytime may be set as from 6:00 a.m. to 8:00-
~~p.m.~~ p.m. and nighttime from 8:00 p.m. to 6:00 a.m., for example, thus

enabling fine-tuned control of the audio output level according to the user's life pattern, such as a relatively large threshold for daytime and a small threshold for nighttime.

Naturally, setting three or more thresholds and more minute clock
5 | time information to be associated ~~allow~~ therewith allows for further finer-tuned control of the audio output level.

The upper limit of the audio output level may be changeable according to a connected device. For different signal levels by device, such as audio equipment with various devices connected, the upper
10 | limit of the audio output level may be separately set ~~by~~ for each device.

~~In this case, it~~ This case is adequate acceptable as long as ~~these the~~ thresholds are set and stored ~~being associated~~ in association with the information for the audio output ~~device~~ devices using ~~its threshold~~ these thresholds. As a result, comparing the information about which
15 | audio output device is currently ~~outputting~~ outputting with its ID number, which is allocated for identifying the device, assuming that the target equipment using the present invention incorporates plural audio output devices such as a CD player and radio receiver, allows the audio output level to be controlled using the optimum threshold for the
20 | device.

Allocating a relevant ID number also to the audio input terminal allows the audio output level to be controlled as well, even if an external audio output device is connected.

In the above description, the upper limit of the audio output level
25 | is to be preliminarily set. However, the lower limit can be preliminarily set as well. In this case, if the setting is made so that the ~~value~~ audio output level is lower than the lower limit when

decreasing the volume level, it is ~~adequate~~ acceptable as long as a request is made to the operator for an acknowledgement that the operation is appropriate, and if a reply is given, the setting is made so that the value is lower than the lower limit.

5 As described above, the method of setting the audio output level and the device for setting the audio output level according to the present invention ~~allow preventing~~ prevent an error in setting the audio output level due to an operating error, by making a request for an acknowledgement that the volume adjustment currently intended is
10 appropriate.

SECOND EXEMPLARY EMBODIMENT

A description ~~will be made~~ is provided for a method of setting the audio output level according to a second exemplary embodiment of the present invention, using Fig. 3. Fig. 3 shows operation state judging means 8 newly added to Fig. 1. Accordingly, ~~a~~ the detailed description is omitted for ~~a part~~ the parts with ~~a makeup~~ the same makeup as that in Fig. 1.

The second exemplary embodiment is different from the first one in that signals from operation state judging means 8 are connected to
20 volume setting means 2. In the first exemplary embodiment, the setting of the volume output by the device is made according to an operation instruction from volume adjuster 1.

Meanwhile, in the second exemplary embodiment, the volume level
25 is set according to instructions from operation state judging means 8, in addition to those from volume adjuster 1.

In Fig. 3, operation state judging means 8 gives notice to volume

setting means 2 that it is immediately after the power is turned on. A description is made for the actions of volume setting means 2 using the flowchart in Fig. 4.

Volume setting means 2 identifies a state immediately after the power is turned on, by detecting signals from operation state judging means 8 (step 202).

Volume setting means 2 checks the audio output level setting when the power is turned on, and ends setting of the audio output level if it is lower than the upper limit of the audio output level preliminarily set (steps 203 and 205).

Meanwhile, volume setting means 2 changes the audio output level, and then ends setting of the audio output level if it exceeds the upper limit thereof preliminarily set (steps 203, 204, and 205).

The changed audio output level may be the upper limit of the audio output level or a separate one preliminarily set.

When audio signals ~~are to be output being~~ are selected from among plural kinds, the output level can be separately set by kind of signals at a connection source. Here, plural kinds of audio signals refer to audio signals such as those from a radio receiver and compact disc player, for audio equipment; and those from satellite and terrestrial broadcasting, and from video equipment, for television.

Meanwhile, in the above description, operation state judging means 8 is to give notice to volume setting means 2 that it is immediately after the power is turned on. However, operation state judging means 8 may give notice to volume setting means 2 that the power has been turned on only when the power is cycled after a certain period of time. Here, a certain period of time is to be 15 to 30 minutes

or longer, for example. This makeup prevents the volume level setting ~~made immediately before~~ that has been recently set from being changed if the power is frequently ~~cycled~~, cycled by dispensing with resetting of the volume level every time the power is turned ~~on~~ on,
5 despite a slight change in operation environment of the device.

As a concrete example for operation state judging means 8, the case is shown where judgement is made that it is immediately after the power is turned on. However, besides detecting a state in which the power is turned on and off, detecting may be made that no operation
10 has been performed for a certain period of time. Alternatively, judgement may be performed as to whether the elapsed time from the last audio output to the new one exceeds a certain period of time. This makeup may be applied to a cell phone, for example, where continuous audio output is not necessarily made while the power is on.

15 Here, a telephone call on a cell phone is taken as an example. When the audio signal output level is set so as to exceed the upper limit of the audio output level preliminarily set, for some reason in the previous telephone call, the audio signal level may be reset to the audio output level preliminarily set in the next call. This prevents sound
20 with a volume level higher than necessary from being unexpectedly output in an environment for the next call, due to a change from the previous call in ambient environment.

Hereinbefore, the description is has mainly ~~made for~~ been related to the case where the audio output level is increased. However, it is
25 obvious that the same method can be applied for the case where the audio output level is decreased, inversely.

When upper and lower limits ~~are set~~ of the audio output level are

~~set to be suitable in~~ for an ordinary environment, and if the audio output level exceeds the upper or lower limit, the method in the description hereinbefore can be applied.

In this exemplary embodiment, setting and storing plural
5 thresholds with information about time and the audio output device to
be associated therewith, allow for further finer-tuned control of the audio output level.

THIRD EXEMPLARY EMBODIMENT

10 A description ~~will be made~~ is provided for a method of setting the audio output level according to a third exemplary embodiment of the present invention, using Fig. 5. Fig. 5 shows reception state judging means 9 and receiver 10 newly added to Fig. 1. Accordingly, ~~a the~~
detailed description is omitted ~~for a part~~ the parts ~~with a makeup~~ the
15 same makeup as that in Fig. 1.

The third exemplary embodiment is different from the first one in that signals from reception state judging means 9 are connected to volume setting means 2, and that signals from receiver 10 are connected to reception state judging means 9. In the first exemplary
20 embodiment, the setting of the volume output by the device is made according to operation instructions from volume adjuster 1.

The third exemplary embodiment relates to a method of setting the audio output level when a volume adjustment is made in a device equipped with an audio output function, such as a television set or
25 audio equipment, particularly assuming that the audio output level is changed according to reception conditions in broadcasting.
Accordingly, in the third exemplary embodiment, volume setting means

2 sets the volume level according to instructions from reception state judging means 9 in addition to those from volume adjuster 1.

Reception state judging means 9 gives instructions to volume setting means 2 according to information from receiver 10.

5 Hereinafter, a description of this exemplary embodiment will be made for a case where TV broadcasting is being viewed on a mobile object such as an automobile. When receiving TV broadcasting on a mobile object, reception conditions largely change with its movement. Poor reception conditions cause interruption in sound and image.

10 When receiving digital broadcasting in particular, interruption in sound and image occurs if the receive signal quality decreases below a certain level. In this case, ~~such~~ control is usually performed such that an image having been received until immediately before the decrease is output as a still image and audio output is not made. Here, when

15 receiving the conventional analog broadcasting, where degradation in sound and image gradually emerges according to degradation in-
~~receive~~ received signal quality, viewers can recognize degradation in reception quality relatively easily.

As mentioned above, when receiving digital broadcasting, a still

20 image and silence may mislead a viewer into believing that the silence is caused by the low audio output level and into trying to increase the volume level.

Under ~~the~~ these circumstances, receiver 10 shown in Fig. 4 gives notice of the reception state of broadcasting to reception state judging

25 means 9. Reception state judging means 9 detects signals from receiver 10 and then gives notice of the reception state to volume setting means 2.

A description ~~will be made~~ is provided for the actions of volume setting means 2, using Fig. 6. Volume setting means 2 detects that a request has been made for changing the audio output level (step 302). Volume setting means 2 detects signals from reception state judging
5 means 9 to check the current reception conditions (step 303). If the broadcast is being normally received, the process changes the audio output level (step 304), and then ends setting of the audio output level (step 306).

Meanwhile, if the broadcast is not ~~normally~~ being normally
10 received, the process gives notice that the audio output level will not be changed (step 305), and then ends setting of the audio output level (step 306).

Here, the notice that the audio output level will not be changed may be given with characters on the screen of a display unit or with
15 sound.

This method solves the following problem. That is, if the audio output level has been changed while the device is controlled to be in a silent state ~~for its controlling, releasing~~ ending the silent state causes too large a sound to burst out from the device.

20 The actions of volume setting means 2 can ~~be~~ also be the processes in Fig. 7. Volume setting means 2 detects a request for changing the audio output level having been made (step 402). Volume setting means 2 detects signals from reception state judging means 9 to check the current reception conditions (step 403). If the broadcast is
25 normally being received, the process changes the audio output level (step 404), and then ends setting of the audio output level (step 407).

Meanwhile, if the broadcast is not normally being received, the

process makes a request for an acknowledgement that the operation for changing the audio output level is appropriate (step 405), and if the operator selects continuing of the change operation, the process changes the audio output level (step 404), and then ends setting of the audio output level (step 407).

Meanwhile, in step 405, if the operator does not select continuing of the change operation, the process gives notice of the discontinuing of the level change (step 406), and then ends setting of the audio output level (step 407).

The method of giving notice that the audio output level will not be changed is to be the same as that in Fig. 6. The notice of discontinuing the change of the audio output level in step 406 can be omitted.

The above method solves the following problem. That is, if the audio output level has been changed while the device is controlled to be in a silent state ~~for its controlling, releasing~~ ending the silent state unexpectedly causes too large a sound to burst out from the device.

Here, the description is made for the case where digital TV broadcasting is received on a mobile object as the third exemplary embodiment. However, this exemplary embodiment can be applied to another type of usage. Further, the first exemplary embodiment can be combined with the second one.

INDUSTRIAL APPLICABILITY

A method of setting the audio output level and a device for setting the audio output level of the present invention eliminate an error in setting the audio output level due to an operating error, and prevent

sound with an inappropriate volume level from being output when the device is subsequently used ~~next time~~ or when the reception state ~~becomes improved~~ improves, which is useful for devices with an audio output ~~function~~ function, in general.

ABSTRACT

In a device equipped with an audio output, a range of the audio output level in regular use is set. When an attempt is made to change the setting to a volume level exceeding the range of the audio output level having been set, a request is made for an acknowledgement that the operation is appropriate, and only if a reply is ~~given~~ received within a given time, ~~the volume setting is~~ the volume setting changed. Such a method prevents the audio output from a television set or audio equipment to be increased to a volume level higher than necessary due to an operating error in a volume setting operation.